

ELECTRONIC RETURN DAMPER ACTUATOR

20 Nm | 2-POINT CONTROL



The appearance of the product may differ from the illustration. Technical specifications are subject to change.

NECA...20 (S) SERIES

NECA series actuators with Electronic Return® (ER) function are designed and produced for extended functionalities in HVAC systems fan coil and laboratory applications.

Electronic Return® (ER) is able to manage short voltage interruptions for max. 4 seconds. In case of longer voltage interruption actuator will move the damper or valve to a predefined emergency position (EPS).

- Torque 20 Nm.
- For damper size ca. 4,0 m².
- Power supply 24 V_{AC/DC} and 230 V_{AC}
- 2-point control.
- Manual over-ride push button.
- Shaft dimension: Ø 12...20 mm / square 11...14 mm.
- Minimum shaft length 50 mm.
- Selectable direction of rotation by switch.
- Adjustable angle of rotation.
- Actuator available with 1 m connection cable.
- Optional 2 adjustable SPDT auxiliary switches.
- Customised versions and functions (on request).



MODEL SELECTION TABLE

Torque	Running time	Return time – safety function	Power supply	Auxiliary switches	Model/type
20 Nm	90...125 s	70 s	24 V _{AC/DC} ± 10%	No	NECA 1-20
20 Nm	90...125 s	70 s	24 V _{AC/DC} ± 10%	2 x SPDT (adjustable)	NECA 1-20S
20 Nm	90...125 s	70 s	230 V _{AC} ± 10%	No	NECA 2-20
20 Nm	90...125 s	70 s	230 V _{AC} ± 10%	2 x SPDT (adjustable)	NECA 2-20S



ELECTRONIC RETURN DAMPER ACTUATOR

20 Nm | 2-POINT CONTROL

ACTUATOR DIMENSIONS [mm]



TECHNICAL SPECIFICATION


	NECA 1-20 (S)	NECA 2-20 (S)
Torque	20 Nm	20 Nm
Damper size	4.0 m ²	4.0 m ²
Shaft dimensions	Ø 12...20 mm / square 11...14 mm	Ø 12...20 mm / square 11...14 mm
Power supply	24 V _{AC/DC} ± 10%	230 V _{AC} ± 10%
Frequency	50...60 Hz	50...60 Hz
Control signal (input)	2-point control	2 point control
Power consumption		
– Operating	7.2 W	7.2 W
– At end position	1.2 W	1.2 W
Rated power	10.0 VA	10.0 VA
Auxiliary switches rating	3(1.5) A/250 V _{AC}	3(1.5) A/250V _{AC}
Protection class	III 	II 
Electrical wiring	1 m Cable	1 m Cable
Angle of rotation	90° (95° mechanical limitation)	90° (95° mechanical limitation)
Weight	1.2 kg	1.2 kg
Durability	60,000 rotations	60,000 rotations
Sound level	< 45 dB	< 45 dB
Protection degree	IP54	IP54
Working temperature range	-20°C...50°C as per IEC 721-3-3	-20°C...50°C as per IEC 721-3-3
Storage temperature	-30°C...+60°C / IEC 721-3-2	-30°C...+60°C / IEC 721-3-2
Humidity	5...95% rH (non condensing) / EN	5...95% rH (non condensing) / EN
Maintenance	Maintenance free	Maintenance free
Principle of operation	Type 1 (acc. to EN 60730-1)	Type 1 (acc. to EN 60730-1)
Electromagnetic compatibility	CE & ISO 9000 to EN / EEC	CE & ISO 9000 to EN / EEC

ELECTRONIC RETURN DAMPER ACTUATOR

20 Nm | 2-POINT CONTROL

Wiring diagram NECA...20 (S1)


Power supply 24 V_{AC}/DC / 230 V_{AC}



⚠ Connect via safety isolating transformer.



■ Changing direction of rotation NECA ...20 (S)

Direction of rotation can be changed by toggling the CW/CCW switch on the actuator housing.




Wiring Diagram NECA...20 (S)

Auxiliary switches



3 (1.5) A / 250 V_{AC}
Actuator at 0° position

■ Auxiliary switches NECA ...20 (S)




■ Note

Parallel connection of maximum five NECA...20 is possible.
Power consumption must be observed!

Wiring Diagram NECA...20 (S)


Parallel connection




ELECTRONIC RETURN DAMPER ACTUATOR

20 Nm | 2-POINT CONTROL

■ Limiting angle rotation NECA ...20 (S)



■ Installation instruction



⚠ IMPORTANT REMARKS

This actuator includes electrical and electronic components and may not be disposed as household waste. Please consider the local valid legislation.

24 V_{AC/DC}: Connect via safety isolating transformer.

230 V_{AC}: To isolate from the main power supply, the system must incorporate a device which disconnects the phase conductor (with at least a 3 mm contact gap.)

Consult NENUTEC representatives for specific requirements and material selections for your intended application. The entire content of this technical datasheet is protected by copyright. All rights are reserved ©.

The performance specifications are nominal and conform to acceptable industry standards. Nenutec shall not be liable for damages resulting from misapplication or misuse of its products.



IMPORTANT REMARK

The NENUTEC NECA... actuator series can be equipped with a variety of NENUTEC products as characterized 2-way and 3-way ball valves of NVCB series.

Contact NENUTEC representatives or factory for the specific requirements and material selection for your intended application.

CUSTOMISED VERSION

NENUTEC offers you actuators in customised versions, e.g. with your own brand name, with colour-coordinated applications and with your particular demand on request.

For further information please contact us or our local representative.

Nenutec Polska

00-236 Warszawa
ul. Świętojerska 5/7
tel.: +48-(0)-504-050225
nenutec@nenutec.pl